

Highlights

EOD robot telemax 4x4

COBHAM



Proven true: less is more!

telemax 4x4:
the latest member of the telemax family

Now even more

- cost-effective
 - speedy
 - lightweight
 - silent
 - enduring
-

Featuring

- 4-wheel drive running gear with a top speed of up to 11.5 km/h
- world-famous telemax manipulator arm with its outstanding capabilities such as TCP control and automatic tool change
- great choice of same tools, accessories and sensors as for all members of the telemax family
- RoboLan, our state of the art WLAN-based data and video transmission
- option to upgrade the system step by step to a telemax PRO or telemax CBRN

Technical data

Length	1020 mm (system in packing position)
Width	605 mm
Height	815 mm (system in packing position w/o options)
Weight	64.5 kg (w/o battery, with RoboLAN module) 63.8 kg (w/o battery, w/o RoboLAN module)
Speed	standard speed version: max. 4.5 km/h high-speed version: max. 11.5 km/h
Drive	4 wheels
Turning circle	1200 mm
Mobility (slopes)	38° (standard speed version, depending on surface)
Mobility (stairs)	17.5°
Mobility (obstacle height)	200 mm
Mobility (gap width)	330 mm
Universal interface	4
Firing channel	3
Fording depth	280 mm
Payload	35 kg (totally)
Power supply	NiMh battery: 24 V, 17 Ah; 10 kg Li-ion battery: 26 V, 13.2 Ah; 3.7 kg Li-ion battery: 26 V, 40 Ah; 8.6 kg

