

Our LRF modules are minimal in weight and size while maintaining top performance – the most important asset when it comes to advanced LRF modules. Our sensors are used in military and civilian applications and have consistently proven their capabilities in the most challenging environments.

More information on ultisense.ch

TULTI SENSE.















RANGE FINDING	LRF 3013	LRF 5020	LRF 3042	LRF 5042	LRF 6019*	LRF 6042*	LRF 7047*
Range performance maximum	5.1 km	4.5 km	6.0 km	10.0 km	15.0 km	25.0 km	30.0 km
Range performance on 2.3 m × 2.3 m target	≥2.8 km	≥2.5 km	≥2.8 km	≥6.0 km	≥6.5 km	≥8.0 km	≥ 11.0 km
Typical accuracy	± 0.75 m	± 3 m	± 3 m	± 3 m	± 1 m	± 1 m	± 1 m
Dimensions (I×w×h)	52×37×22 mm	100×50×35 mm	114×100×50 mm	114×100×50 mm	60×40×45 mm	99×56×52 mm	93×68×87 mm
Weight	45 g	120 g	325 g	325 g	100 g	300 g	460 g

^{*} Innovative fiber laser technology

Illustrations, descriptions and technical data are not binding and may be changed. Copyright © 2021 Safran Vectronix AG, Heerbrugg, Switzerland, All rights reserved – EN – Version D – 12.2021

